ES5462 MFP Specifications





For the businesses that require a 4-in-1 multifunctional device that offers a low total cost of ownership, high quality document output and management at faster speeds of up to 30ppm the ES5462 MFP is the smart choice. Combining a wide range of functions and useful business tools, this device offers superior printing speeds, media flexibility and high capacity toners to support larger workgroups.

The ES5462 MFP is built on tried and tested technology that your business can rely on to deliver over and over again.

Outstanding features to support your business needs

- Automatic Duplex printing, copying, scanning and faxing as standard with colour print speeds up to 26ppm
- 50-sheet Reverse Automatic Document Feeder (RADF) for quick and easy copying and scanning double-sided documents
- Time to first print, 8 seconds colour,7.5 seconds mono
- Intuitive menus and controls with one touch function buttons and 3.5" LCD display for simple user interface
- Print directly from or scan directly to a USB stick

Excellent print quality and media flexibility

- Duplex as standard (up to 176gsm), for in-house professional printing
- ProQ2400 multi-level output quality, 1200 x 600dpi print resolution
- Microfine High Definition toners for superb print quality
- Flexible media handling: from A6 to 1320mm banners; card stock up to 220gsm
- OKI Template Manager makes it easy to create and print various documents in-house

Functionality to improve your productivity and workflow

- High quality, copying, scanning and faxing using LED digital technology
- Overlay function enables you to save logos or forms in the MFP's memory, for re-use in other documents
- Job Macro enables the user to programme frequently used copy settings
- Super G3 speed fax for high speed delivery and receipt
- Send faxes over the internet
- Fast scan speed of up to 20ppm colour and 30ppm mono
- LDAP direct access to contact and email data from an existing server directory
- USB and network TWAIN scanning (PC and Mac)

- ID card copying for simple copying of double sided ID cards on a single sheet
- Document collation automatically sorts copies of multi-page documents

Efficient and cost saving functionality

- Eco Mode improves throughput performance and reduces energy consumption
- Deep Sleep Mode reduces energy consumption to less than 1.5W
- Auto-Off mode automatically powers down from Deep Sleep, reducing energy consumption to 0.5W when not in use
- High capacity 7K black toner cartridge and up to 30K black drum

Useful utilities that help you control and manage your printing

- PrintSuperVision that helps you control and resolve issues with printers across your networks
- Print Job Accounting provides visibility and control of your organisation's print spend across your network
- Secure Print function for PIN or password protected printing











ES5462 MFP - Colour and Mono Multifunction Product

| 24nnm colour 20nnm mono | TYPEFACES | Coolable 07 DCI Forth and 00 D 10 11 ft 1 DCI 20 |
|---|--|---|
| | Printer fonts | Scalable: 87 PCL Fonts and 80 PostScript fonts, PCL Bitmap fonts: Lineprinter OCR-A/B, USPS ZIP Barcode |
| Up to 60 seconds from power on and up to 32 seconds from power save | Barcode | 12 types of one dimension with 28 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET, Customer barcode; 1 type of two dimension: PDF417 |
| 533MHz | | |
| | PRINT QUALITY | |
| 1200 x 1200dpi | Resolution | ProQ2400 Multi-level Technology, 1200 x 600dpi, 600 x 600d |
| Up to 20ppm colour, up to 30ppm mono | Enhancements | Auto Color Balance, Photo Enhance via driver |
| Input 48-bit / Output 24-bit | | (excludes PostScript driver) |
| 50-sheet Reverse Automatic Document Feeder (RADF), flatbed scanner | PAPER HANDLING | Tray 1: 250 sheets of 80gsm; Multi-purpose tray: 100 sheets |
| 7 Levels | | of 80gsm; RADF: 50 sheets of 80gsm |
| PDF, M-TIFF, JPEG, XPS | | 530 sheets of 80gsm |
| LDAP, 100 E-mail address, 20 group addresses | Maximum paper capacity | 880 sheets of 80gsm |
| FTP, HTTP, USB memory, E-mail, TWAIN, CIFS | Paper sizes | Tray 1: A4, A5, B5, A6; Tray 2: A4, A5, B5; Multi-purpose tray: A A5, B5, A6, Envelopes (C5, DL, Com-9, Com-10, Monarch), Inde: Card (3" x 5") (75 x 125mm), Photo Size (4" x 6", 5" x 7") (100 x 150mm, 125 x 175mm), Custom Size (up to 1320mm length |
| | | including banners); Duplex: A4, A5, B5; RADF: A4, A5, B5, A6 |
| Up to 600 x 600dpi | Paper weight | Tray 1/2: 64 to 176gsm; Multi-purpose tray: 64 to 220gsm; Duplex: 64 to 176gsm; RADF: 60 to 105gsm |
| Zoom 25-400% | Duplex | Standard |
| 99 | Paper output | Face Down: 150 sheets of 80gsm; Face Up: 100 sheets of 80gsm |
| | GENERAL FEATURES | |
| RJ11 x 2 (Line/Tel), PSTN, PBX Line | Memory | Standard RAM: 256MB; Maximum RAM: 768MB |
| ITU-T G3(Super G3) up to 33.6kbps, 3 seconds/page | | Standard SDHC Memory Card ⁴ : 4GB; |
| 16 one touch dials (8 x 2 using shift key), 100 speed dials | | Maximum SDHC Memory Card4: 16GB |
| Up to 20 | Environment | Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended)/ 20% to 80% RH (50% to 70% RH recommended) |
| Maximum 100 | | Storage temperature/ humidity: -10°C to 43°C/ 10% to 90% RI |
| Page memory 4MB (approx. 200 pages transmit and receive) | Power supply | Single phase 220 to 240VAC, frequency 50-60Hz +/- 2% |
| | Power consumption | Typical: 570W; Max: 1170W; Idle: 100W; Power Save: <20W; Deep Sleep: <1.5W; Auto-Off: <0.5W |
| 84.1mm (W) x 33.6mm (H); Resolution: 320x128 dots | Noise level | Operating: 52dB(A) or less (copy); Standby: 33dB(A); Power save: Inaudible |
| Print, Fax), Color & Mono Start, Status, Setting, Help, Job Macro, One Touch & Shift keys, 6 main navigation buttons (Back, Up, | Dimensions (HxWxD) | 444 x 427 x 509mm |
| | | <29kg approx |
| Full Qwerty Key Pad | Warranty | 1 year |
| | | ES5462dn: 01328401 |
| 10/100 TX Ethernet, USB 2.0 Device IE USB 2.0 Host IE | Accessories (Order Number | is) |
| | 2nd paper tray | 44472102 |
| SIDM (IBM-PPR, EPSON-FX) | Cabinet | 01314101 |
| All major network protocols supported via ethernet card with | Memory | 256MB: 01182907; 512MB: 01182908 |
| Network & protocols agement. TCP/IPv4&v6, SMTP, POP3, HTTP, SNMPv1&v3, DHCP, DNS, LPR, Port9100, BOOTP, ARP, FTP, CIFS, LDAP, SLP, Bonjour. | SDHC Memory Card ⁴ | 16GB: 01272701 |
| NetWare, EtherTalk, NetBEUI, LLTD, Web Service on Devices | CONSUMABLES (ORDER NUMBE | rs) |
| / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / | Toner cartridges* (6,000 pages) | Cyan: 44973511; Magenta: 44973510; Yellow: 44973509 |
| X 10.3.9 to 10.7 | Toner cartridge* (7,000 pages) | Black: 44973512 |
| IP Filtering, MAC Filtering, SSL/TLS, NIC Driver (IC+), | Image drum** | 01282903 |
| WindowsRally EmailAlert, EAP(IEEE802.1X), IPSec | | |
| WindowsRally EmailAlert, EAP(IEEE802.1X), IPSec Template Manager ² , Color Correct, OKI LPR ² , Color Swatch | Transfer Belt (60,000 pages) | 44472202 |
| | Fuser Unit (60,000 pages) *Toner: A4 pages yield complian | 4447202 44472603 at with ISO/ISC 19798. Printer shipped with toner for 2,000 A4 pa sper job from tray 1 in simplex mode (30,000 pages black; |
| | Up to 60 seconds from power on and up to 32 seconds from power save 533MHz 1200 x 1200dpi Up to 20ppm colour, up to 30ppm mono Input 48-bit / Output 24-bit 50-sheet Reverse Automatic Document Feeder (RADF), flatbed scanner 7 Levels PDF, M-TIFF, JPEG, XPS LDAP, 100 E-mail address, 20 group addresses FTP, HTTP, USB memory, E-mail, TWAIN, CIFS Less than 14 seconds colour, less than 12 seconds mono Up to 26cpm colour and up to 30cpm mono Up to 600 x 600dpi Zoom 25-400% 99 RJ11 x 2 (Line/Tel), PSTN, PBX Line ITU-T G3(Super G3) up to 33.6kbps, 3 seconds/page 16 one touch dials (8 x 2 using shift key), 100 speed dials Up to 20 Maximum 100 4MB (approx. 200 pages transmit and receive) Single simplified blue backlit graphics panel: 84.1mm (W) x 33.6mm (H); Resolution: 320x128 dots 12 alpha/numeric keys, 4 main function buttons (Copy, Scan, Print, Fax), Color & Mono Start, Status, Setting, Help, Job Macro, One Touch & Shift keys, 6 main navigation buttons (Back, Up, Down, Left, Right, OK), Clear, Stop, Power Save, Reset/Log Out; Full Qwerty Key Pad 10/100 TX Ethernet, USB 2.0 Device IF, USB 2.0 Host IF PCL6 (XL3.0), PCL5c, PostScript 3 (clone), SIDM (IBM-PPR, EPSON-FX) All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPV4&v6, SMTP, POP3, HTTP, SNMPV1&v3, DHCP, DNS, LPR, Por19100, BOOTP, ARP, FTP, CIFS, LDAP, SLP, Bonjour, NetWare, EtherTalk, NetBEUI, LLTD, Web Service on Devices Windows XP (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Wista (32-bit & 64-bit) / Wi | 8 seconds colour, 7.5 seconds mono Up to 60 seconds from power on and up to 32 seconds from power save seconds from power on and up to 32 seconds from power save Barcode 1200 x 1200dpi |

¹Check local OKI Executive Series website for latest driver releases and OS compatibility; ²Windows only; ³Mac only; ⁴Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non OKI genuine SDHC Memory Card; ³Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI EUROPE LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F +44(0) 20 8219 2199

WWW.OKIEXECUTIVESERIES.COM

